

EXCEED6040 AMBIENT TEMP PnP HANDLER



Product Features:

1. High Precise Fiber Optic Sensor
 - The floating scope bigger and more accurate
2. Quick Change-Over
 - Kit Change time Approx. 10mins
 - Perfect compatible with all standard kit
3. Good Operator Friendly and Efficiency
 - All 6 Tray Loaders & Un-Loaders are auto;
 - Jam Rate < 1/ 15,000 pcs
4. Octal Site Upgradable
 - JHT Quad-sites pre-configured handler can upgrade to octal sites.
5. Mute Track
 - Reduce Machine noise and friction.

Standard Specifications:

Basic Specifications	
Model	EXCEED-6040
Device Type	QFP, TQFP, CSP, PLCC, QFN, BGA, LGA, PGA, TSOP
Package Size	Min.2x2mm - Max. 55x55mm
Test Sites	Square Quad (2x2) Sites; Inline Quad (1x4) Sites; Dual Sites; Single Sites.
Socket Area	210 x 135mm
Mechanical Index Time	0.38 sec. (Depends on the socket mounting height)
Max. Throughput	UPH 8500pcs/hour(room) (Test Time = 0sec)
Tray Loader/Un-loader	2 auto loaders and 4 auto un-loaders; Elevating auto loading and unloading (Stack up to 20 trays)
Temperature	Ambient
Standard Tray Size	JEDEC
Binning	16 software binning; 6 physical binning positions (3 auto and 3 fixed trays)
Power	220VAC single phase 50/60Hz 30A
Tester Interface	TTL / GPIB/RS232/Network
Handler Dimensions	1700mm(L)*1400mm(W)*2000mm(H)
Weight	Approx. 1000kg

www.jhtsemiconductor.com